

WATERAX

B2X 18 HP



PRODUCT SELECTION MATRIX

		B2X-18 Vehicle Mount Horizontal Drive				B2X-18 Vehicle Mount Vertical Drive				B2X-18 Portable			
		B2X-18H	B2X-18HT	B2X-18HX	B2X-18HXT	B2X-18V	B2X-18VT	B2X-18VX	B2X-18VXT	B2X-18P	B2X-18PTC	B2X-18PXTC	B2X-18PETC
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 50 PSI (3.4 BAR)				255 GPM (965 lpm)							
		Flow @ 100 PSI (6.9 BAR)				155 GPM (587 lpm)							
		Flow @ 150 PSI (10.3 BAR)				65 GPM (246 lpm)							
		Maximum Pressure				190 PSI (13.1 BAR)							
		Maximum Flow				300 GPM (1136 lpm)							
	Pump Type	High Pressure - Medium Flow				2-Stage Centrifugal Pump							
	Pump Standard Connections	Intake				3" Female NPT/4" VIC Combination							
		Discharge				2-1/2" Female NPT/3" VIC Combination							
	Engine Type	Air Cooled Gasoline				B&S Vanguard							
	Engine Max Power	[Torque]				18 hp (13.4 KW) @ 4000 RPM [26.9 lb-ft (36.5 Nm) @ 2800 RPM]							
Drive	Orientation (timing belt, 1.88 : 1 speed increasing ratio)				Horizontal				Vertical				
Frame	Base Mount with Industrial Isolators				Base Mount with Industrial Isolators				Carry Frame				
Dry Weight*	153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	167 lbs (76 kg)	172 lbs (78 kg)	176 lbs (80 kg)	194 lbs (88 kg)	

* Approximated and varies based off option selections

		B2X-18H	B2X-18HT	B2X-18HX	B2X-18HXT	B2X-18V	B2X-18VT	B2X-18VX	B2X-18VXT	B2X-18P	B2X-18PTC	B2X-18PXTC	B2X-18PETC	
OPTIONS	Primer	Guzzler Hand Primer	-	-	-	-	-	-	-	S	S	-	-	
		Remote Exhaust Primer w/Control Cable	-	-	S	S	-	-	S	S	-	-	-	-
		Exhaust Primer	-	-	-	-	-	-	-	-	-	S	-	-
		Electric Package - Electric Primer, LED work light, & Battery	-	-	-	-	-	-	-	-	-	-	S	-
	Muffler	Horizontal low tone	S	S	-	-	-	-	-	S	S	-	-	
		Dual low tone	-	-	-	-	S	S	-	-	-	-	-	
		Exhaust primer muffler	-	-	S	S	-	-	S	S	-	-	S	S
	Fuel Tank	Integral / 1.75 US gallons (6.6 L)	-	S	-	S	-	S	-	S	-	S	S	S
		Integral / 1 US gallon (3.8 L) w/ 3-way valve	-	-	-	-	-	-	-	-	-	-	-	-
	Controls	Engine Mount Control Panel	-	-	-	-	-	-	-	-	S	S	S	S
Remote Mount Control Panel - XCP Series		-	-	-	-	0	0	0	0	-	-	-	-	
Discharge Gauge	0-600 psi, 2-1/2" dial	-	-	-	-	-	-	-	S	S	S	S		
FastWire CTRL Cable	B&S 3' CTRL Cable with 8 pin connector (FWC-B-3)	S	S	S	S	S	S	S	S	-	-	-	-	
	Honda GX630 3' CTRL Cable with 8 pin connector (FWC-H-3)	-	-	-	-	-	-	-	-	-	-	-	-	

Standard S
Option O
Not Applicable —



WE MOVE WATER

WATERAX

All information contained in this document including drawings is proprietary to *WATERAX* and may not be copied, reproduced or used in whole or in part without our prior written permission. The information in this document is subject to change without notice. Model displayed with multiple options. Weight and dimensions are approximated and may vary depending on options.

WATERAX INC.
6635 Henri-Bourassa W.
Montreal, QC H4R 1E1
T 514 637-1818
F 514 637-3985
TF 1 855 616 616-1818
info@waterax.com

waterax.com

To help you stay **#ReadyForWildfires**, we've made a few changes, placing 100% of our focus on manufacturing our core products, portable fire pumps. To do so, we've established a network of trusted supply and distribution partners that can help us provide *WATERAX* pumps quickly in addition to water-handling equipment and accessories.

For immediate assistance when it comes to pumps and water-handling accessories, please [contact your local dealer](#).

For genuine spare parts, visit our [online store](#).

B2X™ is a trademark of Waterax.



**WE MOVE
WATER**