

# WATERAX

## BB-4<sup>®</sup> 18 HP



### PRODUCT SELECTION MATRIX

		BB-4-18 Vehicle Mount Horizontal Drive				BB-4-18 Vehicle Mount Vertical Drive				BB-4-18 Portable			
		BB-4-18H	BB-4-18HT	BB-4-18HX	BB-4-18HXT	BB-4-18V	BB-4-18VT	BB-4-18VX	BB-4-18VXT	BB-4-18P	BB-4-18PTC	BB-4-18PXC	BB-4-18PETC
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 150 PSI (10.3 BAR)	100 GPM (379 lpm)										
		Flow @ 250 PSI (17.2 BAR)	83 GPM (303 lpm)										
		Flow @ 350 PSI (24.1 BAR)	50 GPM (189 lpm)										
		Maximum Pressure	440 PSI (30.3 BAR)										
		Maximum Flow	106 GPM (401 lpm)										
	Pump Type	High Pressure - Medium Flow 4-Stage Centrifugal Pump											
	Pump Standard Connections	Intake	2" Male NPSH										
		Discharge	1-1/2" Male NPSH										
	Engine Type	Air Cooled Gasoline B&S Vanguard											
	Engine Max Power	[Torque]	18 hp (13.4 KW) @ 4000 RPM [26.9 lb-ft (36.5 Nm) @ 2800 RPM]										
Frame		Base Mount with Industrial Isolators				Base Mount with Industrial Isolators				Carry Frame			
Drive	Orientation (timing belt, 1.88:1 speed increasing ratio)	Horizontal				Vertical				Vertical			
Dry Weight*		153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	153 lbs (69 kg)	157 lbs (71 kg)	157 lbs (71 kg)	161 lbs (73 kg)	167 lbs (76 kg)	172 lbs (78 kg)	176 lbs (80 kg)	194 lbs (88 kg)

\* Approximated and varies based off option selections

		BB-4-18H	BB-4-18HT	BB-4-18HX	BB-4-18HXT	BB-4-18V	BB-4-18VT	BB-4-18VX	BB-4-18VXT	BB-4-18P	BB-4-18PTC	BB-4-18PXC	BB-4-18PETC	
OPTIONS	Primer	Guzzler Hand Primer	-	-	-	-	-	-	-	S	S	-	-	
		Remote Exhaust Primer w/Control Cable	-	-	S	S	-	-	S	S	-	-	-	-
		Exhaust Primer	-	-	-	-	-	-	-	-	-	-	S	-
		Electric Package - Electric Primer, LED work light, & Battery	-	-	-	-	-	-	-	-	-	-	-	S
	Muffler	Horizontal low tone	S	S	-	-	-	-	-	-	-	-	-	-
		Dual low tone	-	-	-	-	S	S	-	-	S	S	-	-
		Exhaust primer muffler	-	-	S	S	-	-	S	S	-	-	S	S
	Fuel Tank	Integral / 1.75 Us gallons (6.6 L)	-	S	-	S	-	S	-	S	-	S	S	S
		Integral / 1 Us gallon (3.8 L) w/ 3-way valve	-	-	-	-	-	-	-	-	-	-	-	-
	Controls	Engine Mount Control Panel	-	-	-	-	-	-	-	-	-	S	S	S
		Remote Mount Control Panel - XCP series	O	O	O	O	O	O	O	O	-	-	-	-
	Discharge Gauge	0-600 psi, 2-1/2" dial	-	-	-	-	-	-	-	-	S	S	S	S
	FastWire CTRL Cable	B&S 3' CTRL Cable with 8 pin connector (FWC-B-3)	S	S	S	S	S	S	S	S	-	-	-	-
		Honda GX630 3' CTRL Cable with 8 pin connector (FWC-H-3)	-	-	-	-	-	-	-	-	-	-	-	-

Standard s  
Option o  
Not Applicable —



**WE MOVE WATER**

# **WATERAX**

All information contained in this document including drawings is proprietary to *WATERAX* and may not be copied, reproduced or used in whole or in part without our prior written permission. The information in this document is subject to change without notice. Model displayed with multiple options. Weight and dimensions are approximated and may vary depending on options.

**WATERAX INC.**  
6635 Henri-Bourassa W.  
Montreal, QC H4R 1E1  
T 514 637-1818  
F 514 637-3985  
TF 1 855 616 616-1818  
[info@waterax.com](mailto:info@waterax.com)

**waterax.com**

To help you stay **#ReadyForWildfires**, we've made a few changes, placing 100% of our focus on manufacturing our core products, portable fire pumps. To do so, we've established a network of trusted supply and distribution partners that can help us provide *WATERAX* pumps quickly in addition to water-handling equipment and accessories.

For immediate assistance when it comes to pumps and water-handling accessories, please [contact your local dealer](#).

For genuine spare parts, visit our [online store](#).

BB-4® is a trademark of Waterax.



**WE MOVE  
WATER**