

# WATERAX

# MINI-STRIKER®



## PRODUCT SELECTION MATRIX

		MINI-STRIKER Vehicle Mount	
		MSTR-V	MSTR-P
SPECIFICATIONS	Performance (standard NFPA Conditions)	Flow @ 25 PSI (1.7 BAR)	68 GPM (257 lpm)
		Flow @ 50 PSI (3.4 BAR)	42 GPM (159 lpm)
		Flow @ 75 PSI (5.2 BAR)	12 GPM (45 lpm)
		Maximum Pressure	85 PSI (5.9 BAR)
		Maximum Flow	80 GPM (303 lpm)
	Pump Type	High Pressure - Medium Flow	1-Stage Centrifugal Pump
	Pump Standard Connections	Intake	1-1/2" Male NPSH
		Discharge	1-1/2" Male NPSH
	Engine Type	Air Cooled Gasoline	Honda GXH50
	Engine Max Power	[Torque]	2.1 HP (1.6 kW) @ 7,000 RPM [2.0 lb-ft (2.7 Nm) @ 4,500 RPM]
Fuel Tank	Integral .2 US gal (0.77 L)	0.2 US Gallon (0.77 L)	
Frame		Industrial Isolators	
Dry Weight*		19 lbs (8.6 kg)	
			Poly base with rubber mount
			20 lbs (9 kg)

\* Approximated and varies based off option selections



# **WATERAX**

All information contained in this document including drawings is proprietary to *WATERAX* and may not be copied, reproduced or used in whole or in part without our prior written permission. The information in this document is subject to change without notice. Model displayed with multiple options. Weight and dimensions are approximated and may vary depending on options.

**WATERAX INC.**  
6635 Henri-Bourassa W.  
Montreal, QC H4R 1E1  
T 514 637-1818  
F 514 637-3985  
TF 1 855 616 616-1818  
[info@waterax.com](mailto:info@waterax.com)

**waterax.com**

To help you stay **#ReadyForWildfires**, we've made a few changes, placing 100% of our focus on manufacturing our core products, portable fire pumps. To do so, we've established a network of trusted supply and distribution partners that can help us provide *WATERAX* pumps quickly in addition to water-handling equipment and accessories.

For immediate assistance when it comes to pumps and water-handling accessories, please [contact your local dealer](#).

For genuine spare parts, visit our [online store](#).

MINI-STRIKER® is a trademark of Waterax.



**WE MOVE  
WATER**